

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

1 Identification

· Product identifier

• Trade name: <u>*UV-5608DC*</u>

· Product number: UV-5608DC

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EPOXYSET INC. 718 Park East Drive

Woonsocket, RI 02895, USA Phone: (401) 726-4500

www.epoxyset.com

· Information department: Product safety department: msds@epoxyset.com

· Emergency telephone number:

Chemtel (US transportation) 1-800-255-3924 International (call collect) +01-813-248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irritation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Epoxy phenol novolac resin

· Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

P321 Specific treatment (see on this label). (Contd. of page 1)

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

28064-14-4 Epoxy phenol novolac resin

>60%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

(Contd. of page 2)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1 Total Action Criteria for Chemicals	
· PAC-1:	
28064-14-4 Epoxy phenol novolac resin	30 mg/m ³
· PAC-2:	
28064-14-4 Epoxy phenol novolac resin	330 mg/m ³
· PAC-3:	
28064-14-4 Epoxy phenol novolac resin	2,000 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store at temperatures not exceeding 10°C. Keep cool.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

(Contd. of page 3)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection: Goggles recommended during refilling.

Physical and chemical proper	
Information on basic physical and	chemical properties
General Information	
Appearance: Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability:	Not applicable.
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

(Contd. on page 5)

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

	(Contd. of page	: 4)
· Partition coefficient (n-octar	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

28064-14-4 Epoxy phenol novolac resin

Oral LD50 >2,000 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

TIC

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

(Contd. of page 5)

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- **Behavior in environmental systems:**
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, IMDG, IATA	UN3082
· UN proper shipping name	
·DOT	Environmentally hazardous substance, liquid, n.o.s. (Epoxy phenol novolac resin)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin)

- · Transport hazard class(es)
- · DOT, IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles

(Contd. on page 7)

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

	(Contd. of page
Label	9
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: Proprieta
	Salt (contains Sb)
Marine pollutant:	Yes (DOT)
1	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler code)	: 90
EMS Number:	F-A,S-F
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: No limit
	On cargo aircraft only: No limit
Remarks:	Special marking with the symbol (fish and tree).
·IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
• • • • • • • • • • • • • • • • • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
8	LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN), 9, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- ·Sara

· Section 355	(extremely	hazardous	substances)):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxio	e Substances Control Act):	
28064-14-4	Epoxy phenol novolac resin	ACTIVE
	2-Oxepanone, polymer with 2-ethyl-2-(hydroxymethyl)-1, 3-propanediol	ACTIVE
	Modified Polyol - Proprietary	ACTIVE
	2-Oxepanone, polymer with 2-ethyl-2-(hydroxymethyl)-1, 3-propanediol	ACTIVE
121239-75-6	Photoinitiator - Proprietary	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

(Contd. on page 8)

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

(Contd. of page 7)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Epoxy phenol novolac resin

· Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

(Contd. on page 9)

Printing date 11/04/2024 Revision 7 Reviewed on 10/11/2024

Trade name: UV-5608DC

(Contd. of page 8)

· Contact: Mr. Patel

· Date of preparation / last revision 11/04/2024 / 6

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of

Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2 Sensitization - Skin 1: Skin sensitisation – Category 1

* * Data compared to the previous version altered.

US